Exova Warringtonfire Aus Pty Ltd Unit 2, 409-411 Hammond Road Dandenong, Victoria 3175 Australia T: +61 (0)3 9767 1000 W: www.exova.com

Postal Address: PO Box 4282 Dandenong South, Victoria 3164 Australia



Testing. Advising. Assuring.

EWFA Test Certificate No.		SFC49581100b.1 Page 1 of 1	
	Report Sponsor	Issue Date	
	Ducab PO Box 11529 Dubai United Arab Emirates	8/01/2018	

Introduction

This test certificate is to verify the element of construction described below was tested by this laboratory on behalf of the test sponsor in accordance with the stated test standard and achieved the results stated below.

Referenced Reports	Report Date	Test Standard
EWFA 49581000b.2	8/01/2018	AS/NZS 3013:2005, Appendix A & B
EWFA Mech 49581100b.1	8/01/2018	AS/NZS 3013:2005, Appendix D & E

Description of Assessed Cable				
Cable Description	 Screened single core cable, 35mm² conductor. Cable overall outer diameter of nominal 13.9mm. Test bending radius of cable: 112mm on the inside of the bend. Mechanical testing temperature range: -25°C to 110°C. Refer to the referenced reports for a full description of tested cable. 			
Cable Configuration	The cable was tested as a single cable for Appendix A & B with two bends of 90° at a bending radius of 112mm. The cable was positioned in the cable tray with a metallic cable tie fixing the cable to the tray at the centre of the two directional changes; otherwise plastic cable ties were used. Refer to the referenced test reports for a full description of cable configuration.			

Cable Classification							
Cable Description	Product Code	Cable Group	Cable Classification				
1C(35mm ²)	Ducab 0.6/1kV 1C × 35mm ² (Design 1)	1	WS52W				

Notes

THIS CERTIFICATE IS PROVIDED FOR GENERAL INFORMATION ONLY AND DOES NOT COMPLY WITH THE REGULATORY REQUIREMENTS FOR EVIDENCE OF COMPLIANCE.

Reference should be made to the relevant test report to determine the applicability of the test result to a proposed installation. The results of these fire tests may be used to assess fire hazard, but it should be recognised that a single test method will not provide a full assessment of fire hazard under all conditions.

TESTING AUTHORITY	Exova Warringtonfire Aus Pty Ltd			
Address	PO Box 4282 DANDENONG SOUTH VIC 3164 Unit 2, 409-411 Hammond Road DANDENONG VIC 3175			
Phone	61 (0)3 9767 1000			
ABN	81 050 241 524			
Email / Home Page	www.exova.com			
Authorisation	Prepared By:	Reviewed By:	Reviewed By:	
	Kailph		Patrih Chan	
	Kai Loh	Anthony Rosamilia	Patrick Chan	

